



就位要求

1. 整机四周距障碍物至少1m。
2. 整机应远离震源。
3. 整机就位场地平整度应不大于5mm。
4. 整机接入电压浮动在±5%以内。
5. 风机及气源请自行放置在不影响使用的位置。
6. 稳压器为非标设备，若选用，位置请与技术部沟通。
7. 本布置图的设备位置仅做参考，实际排放根据现场实际情况而定。

Positioning requirements

1. The distance from obstacles around the entire machine should be at least 1 meter.
2. The whole machine should be kept away from the earthquake source.
3. The flatness of the whole machine in place should not exceed 5mm.
4. The voltage fluctuation of the whole machine's connection is within ± 5%.
5. Please place the fan and air source in a location that does not affect their use.
6. The voltage regulator is a non-standard device. If selected, please communicate with the technical department for its location.
7. The equipment locations in this layout plan are for reference only, and actual emissions will depend on the actual site conditions.



										 山东光耀激光科技有限公司			
标记	处数	分位	更改文件号	签名	年月日	阶段	标记	重量	比例	"图样名称"			
设计			标准件					5718771	1:15	"图样名称"			
校核			工艺							"图样名称"			
工艺设计			审核							"图样名称"			
			批准							"图样名称"			
										共1套	第1套	版本	修改